

5 位數微電腦型盤面式電錶(24X48mm) (5 DIGIT MICROPROCESS PANEL METER, 24x48mm)

MODEL
MMS



特點(FEATURES)

精確度 0.05%滿刻度±1位數(Accuracy 0.05% F.S.±1digit)
 可量測交直流電流/交直流電壓/電位計/傳送器/Pt-100/熱電偶/荷重元/電阻 等信號
 (Measuring DCA/DCV/ACA/ACV/Potentiometer/Transmitter/Pt-100/Thermocouple/Load Cell/Resistor/etc.....)
 顯示範圍 -19999~99999可任意規劃(Programmable rate -19999 to 99999 digit)
 具有自動歸零或保持或雙顯示功能(Auto zero or hold or dual display function)(optional)
 小數點可任意規劃(Decimal point can be modified)
 尺寸小,穩定性高(Dimension small and High stability)

1.MODEL:MMS- (選購型號)

NO	Input Type	NO	DCV(ACV)	NO	DCA(ACA)	NO	Potentiometer	NO	Transmitter	NO	Pt-100	NO	Load Cell	NO	Thermocouple	NO	Aux.Power
A	DC	11	0~50mV	21	0~19.999uA	31	0~10%	41	DC4~20mA	51	-50.00~+50.00	61	2mV/V	71	J(-200~760)	A	AC/DC18~60V
B	AC(RMS)	12	0~5V	22	0~199.99uA	32	0~50%	42	DC1~5V	52	-100.00~+100.00	62	3mV/V	72	K(-200~1360)	B	AC/DC90~260V
C	AC(TRMS)	13	0~10V	23	0~1.9999mA	33	0~100%	43	DC4~20mA	53	-200.0~+400.0	63	2mV/V	73	T(-200~395)		LESS 3VA for AC/DC input
D	Potentiometer	14	0~36V	24	0~19.999mA	34	5~95%	44	DC1~5V	54	-200.0~+850.0	64	3mV/V	74	E(-185~990)		
E	Transmitter	15	0~54V	25	0~199.99mA	35	10~90%	49	SPECIFIED	59	SPECIFIED	69	SPECIFIED	75	R(0~1760)		
F	Pt-100(RTD)	16	0~110V	26	0~2.000A	39	SPECIFIED	41/42 nonexciting DC24V				61/62 Exciting DC5V(<50mA)	76	S(0~1750)			
G	Thermocouple	17	0~600V	27	0~5.000A		Three wire connection	43/44 exciting DC24V (<25mA)		Three wire connection non-programmable		63/64 Exciting DC10V(<50mA)	77	B(200~1800)			
H	Load Cell	18	0~1000V	28	0~7.500A		Exciting voltage DC2.5V(<10mA)										
R	Resistor	19	SPECIFIED	29	SPECIFIED												

2.SPECIFICATION (主要規格)

Measuring accuracy : 0.05% F.S.±1 digit
 (精確度) (23±5) 0.2% F.S.±1 digit(AC(RMS))
 0.2% F.S.±0.5 (CJC)(Thermocouple)
 Sampling time : 16 cycles/sec.
 (取樣時間)
 Readout range : -19999 ~ 99999 digit adjustable
 (顯示值範圍)
 Zero (offset) range : -19999 ~ 99999 digit adjustable
 (歸零調整範圍)
 Over input indication : " doFL " or "-doFL"
 (過載顯示)
 Display : Red high efficiency LEDs high 10.16mm(.4")
 (顯示幕)
 Polarity display : When input is negative " _ " display
 (極性顯示)
 Temp. coefficient : 50ppm/ (0~50)
 (溫度係數)
 Parameter setting : Touch switches
 (參數設定方式)
 Memory mode : Non-volatile E² PROM memory
 (記憶型式)
 Dielectric strength : 1.5KVac/1 min. (input/power)
 (絕緣耐壓能力)
 Operating condition : 0~50 (20 to 90% RH non-condensed)
 (使用環境條件)
 Storage condition : 0~70 (20 to 90% RH non-condensed)
 (存放環境條件)
 CE EMC Certification : EN 55022:1998/A1:2000 Class A
 (CE認證) EN 61000-3-2:2000
 EN 61000-3-3:1995/A1:2001
 EN 55024:1998/A1:2001

3.OUTSIDE DIMENSION AND CONNECTION DIAGRAM (外型尺寸與開孔尺寸與配線圖)

