



Capacity(NM)	d	D	h	H	L	R	b*m*L1*Qty
10/20/30/50	18	115	73	156	200	4.1	6*6*32*2
100	18	115	73	165	200	4.1	6*6*32*2
200/300	28	115	73	170	200	4.1	8*7*32*2
500/700	38	120	73	180	250	6.2	10*8*56*4
1000	48	130	73	188	250	6.2	14*9*56*4

--- Specifications / 规格参数 ---

	Torque/扭矩	Rotating speed/转速
Capacity/量程	10~1000NM	2000RPM
Excitation/激励电压	24V DC	
Zero Balance/零点输出	±1% of F.S.	
Rated Output/额定输出	0~5V	
Nonrepeatability/非重复性	±0.1% of F.S.	
Total Error/综合误差	±0.5% of F.S.	
Temp. Shift Zero/零点温度漂移	±0.01% of R.O./°C	/
Temp. Shift Span/灵敏度温度漂移	±0.01% of R.O./°C	
Input Resistance/输入阻抗	1.0±0.2kΩ	
Output Resistance/输出阻抗	1.0±0.1kΩ	
Insulation Resistance/绝缘阻抗	>5000MΩ(50V)	
Safe Overload/安全过载	120% of F.S.	Rotating speed higher than 2000RPM may cause irreversible damage to the transducer
Ultimate Overload/极限过载	150% of F.S.	
Material of Element/弹性体材料	Aluminum alloy/铝合金	
Working environment/工作环境	-10...+50°C ≤90%RH	
Cable/导线	Ø5*3000mm 4-core shielded cable Ø5*3000mm 4芯屏蔽线	

• Subject to change without notice / 如有更改,不另行通知