


SPECIFICATIONS

Current Rating : 3AMP
 Operation Temperature : -40°C to +105°C
 Contact Resistance : 20mΩ Max.
 Insulation Resistance : 1000MΩ Min
 Withstanding Voltage : AC 1000V
 Insulator Material : Polyester (UL94V-0)
 Standard: PBT
 Contact Material : Bronze
 Contact Plating : Au or Over 50 U" Ni

PIN	A	B	C
10	32.00	21.84	10.16
14	37.08	26.92	15.24
16	39.62	29.46	17.78
20	44.70	34.54	22.86
26	52.32	42.16	30.48
30	57.40	47.24	35.56
34	62.48	52.32	40.64
40	70.10	59.94	48.26
50	82.80	72.64	60.96
60	95.50	85.34	73.66
64	100.58	90.42	78.74

XX X XX X X X X XXXX

Pitch (MM) PA: 0.8*1.2 Male FA: 0.8*1.2 Female PB: 1.0 Male FB: 1.0 Female PC: 1.27 Male FC: 1.27 Female PD: 1.27*2.54 Male FD: 1.27*2.54 Female	Pitch (MM) PE: 2.00 Male FE: 2.00 Female PF: 2.54 Male FF: 2.54 Female PG: 1.778 Male FG: 1.778 Female	Angel Options D: Straight R: Right Angle S: SMT	No. of Positions XX Positions	DIP Spcing 0: NO 1: 1.27MM 2: 2.54MM 3: 7.62MM 4: 10.16MM 6: 15.24MM 9: 22.86MM S: Special	DIP Spcing 0: NO 1: 1.90MM 2: 2.00MM 3: 2.80MM 4: 3.00MM 5: 4.20MM 6: 7.00MM S: Special	Insulator Type 0: NO 1: Single Row 2: Double Row 3: Open frame 4: W/O Bar 5: Special	Pin Plated 0: NO 1: Tin150U" 2: Tin200U" 3: G/F 4: Gold3U" 5: Gold10U" 6: Gold15U" S: Special	Clip Plated 0: NO 1: Tin150U" 2: Tin200U" 3: G/F 4: Gold3U" 5: Gold10U" 6: Gold15U" S: Special	Pin length Options: 0482MM 4.82MM 0540MM 5.40MM S Special
--	--	--	----------------------------------	--	---	--	---	--	---

CODE NO. CUS. NO. SCALE UNIT PAGE	JW00	TOLERANCE: X. ±0.25 .X ±0.20 .XX ±0.05	 深圳市腾菲尔科技有限公司 Shenzhen Teng Phil Technology Co., Ltd. 微信手机: 18025334326 余先生 QQ: 1341092936	TITLE: 2.54mm Ejector Header, Straight	DWG NO. KDD005	THIRD ANGLE PROJECTION	
	None						
	mm						
	1/1						