



UCP200 系列

带座轴承 型号	轴 径		基本尺寸(mm)											螺栓 尺寸 (mm)	重量 (kg)
	d		H	L	J	A	N	N ₁	H ₁	H ₀	B	S	A ₃		
	(in)	(mm)													
UCWP201 202 203		12 15 17	30.2	125	95	32	13	18	13	57	27.4	11.5	—	M10	0.72 0.66 0.66
UCP201 201-8	1/2	12	30.2	127	95	38	13	19	14	61	31	12.7	—	M10	0.76
UCP202 202-9 202-10	9/16 5/8	15	30.2	127	95	38	13	19	14	61	31	12.7	—	M10	0.74
UCP203 203-11	11/16	17	30.2	127	95	38	13	19	14	61	31	12.7	—	M10	0.72
UCP204 204-12	3/4	20	33.3	127	95	38	13	19	14	64	31	12.7	46.4	M10	0.70
UCP205 205-14 205-15 205-16	7/8 15/16 1	25	36.5	140	105	38	13	19	15	71	34.1	14.3	48	M10	0.76
UCP206 206-17 206-18 206-19 206-20	1-1/16 1-1/8 1-3/16 1-1/4	30	42.9	160	121	44	17	21	16	82	38.1	15.9	52	M14	1.25
UCP207 207-20 207-21 207-22 207-23	1-1/4 1-5/16 1-3/8 1-7/16	35	47.6	167	126	48	17	21	17	92	42.9	17.5	59	M14	1.55
UCP208 208-24 208-25	1-1/2 1-9/16	40	49.2	180	137	52	17	21	18	99	49.2	19	68.2	M14	1.90
UCP209 209-26 209-27 209-28	1-5/8 1-11/16 1-3/4	45	54	190	146	54	17	21	20	106	49.2	19	70	M14	2.20
UCP210 210-30 210-31 210-32	1-7/8 1-15/16 2	50	57.2	206	159	60	20	25	21	114	51.6	19	76	M16	2.75
UCP211 211-32 211-34 211-35	2 2-1/8 2-3/16	55	63.5	217	172	60	20	25	23	125	55.6	22.2	76	M16	3.30
UCP212 212-36 212-38 212-39	2-1/4 2-3/8 2-7/16	60	69.9	238	186	70	20	25	24	137	65.1	25.4	89	M16	4.70
UCP213 213-40	2-1/2	65	76.2	262	203	70	25	30	26	149	65.1	25.4	89	M20	5.60
UCP214 214-44	2-3/4	70	79.4	266	210	72	25	30	27	155	74.6	30.2	98	M20	6.60
UCP215 215-47 215-48	2-15/16 3	75	82.6	274	217	74	25	30	28	162	77.8	33.3	97	M20	7.30
UCP216 216-52	3-1/4	80	88.9	292	232	78	25	30	30	174	82.6	33.3	110	M20	9.00
UCP217 217-52	3-1/4	85	95.2	310	247	83	25	30	32	186	85.7	34.1	114.2	M20	10.80
UCP218 218-56	3-1/2	90	101.6	326	262	88	27	30	33	198	96	39.7	124	M22	13.00
UCP220		100	115	380	305	95	30	36	40	225	108	42	—	M24	16.00

备注：1、油嘴位置有90°和45°可选择。 2、可选配通盖或盲盖(S/SM)。