



技术参数:

- 材料: 压铸锌
- 表面处理: 粉末喷涂
- 颜色: RAL 7037 (灰色)
- 温度范围: -40℃ - +125℃
- 防护等级: IP65 (联锁状态, IEC 60529)
- 出线方向: 顶出线
- 出线孔数: 1
- 螺纹规格: M20*1.5
- 联锁元件:
 - 锁扣方式: 单扣
 - 材料: 不锈钢

Technical specification:

- Material: zinc die-cast
- Surface: powder-coated
- Colour: RAL 7037(grey)
- Temperature range: -40℃ - +125℃
- Degree of protection: IP65
(acc.to IEC 60529 for coupled connector)
- Cable entry: top entry
- No. of cable entries: 1
- Thread size: M20*1.5
- Locking element:
 - Locking type: single locking latch
 - material: stainless steel

				表面处理 Finish		-		图号 Drawing No.		-	
				材料 Material		-		产品代号 Part Code		H3A-TE-2B-1L/S-M20	
标记 Mark		处数 Number		变更描述/Description				签名 Signature		日期 Date	
				姓名/Name		日期/Date		姓名/Name		日期/Date	
绘图 Drawn		L CHEN		27.09.2020		标准化 Stand.		-		-	
审核 Checked		HZ LAN		27.09.2020							
工艺 Process		-		-		批准 Approved		HQ ZHANG		27.09.2020	
								比例 Scale		版本 REV.	
								1:1		V1.0	
								重量 Weight		数量 Qty.	
								109g		-	
								All Dimensions in mm Original Size DIN A 4		 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD	